





## Yeastar S Series VoIP PBX

### Simple and Solid IP Phone System for SMB

Easy to use, flexible, and feature-rich S Series is designed to help small and medium businesses make a giant leap in efficiency and cost savings. The innovative S Series provides more flexibility and allows you to connect to traditional lines, VoIP lines, and cellular networks. Perfectly future-proof, S Series converges business-enhancing features with free software updates to grow with your business and assures reliability over the years.

#### Appreciate the Easy-to-use Solution

S Series features fast installation and convenient phone provisioning feature to save you from the laborious trouble of onsite deployment. Intuitive and graphical UI brings point-and-click configuration and maintenance.

#### Your Choice of Technologies and Features

A thorough modular design makes S Series flexible and scalable with your choice of extensions and outside lines. Concurrent calls and maximum users are also expandable to grow with your business.

#### Telephone System without Risk

S Series attends to every detail to ensure the highest quality. Sophisticated design and production process laid the cornerstone, on top of which strict test and inspection processes go hand in hand with quality.

#### Play Safe and Expect Reliability

S Series is protected from Internet hackers, computer viruses, eavesdrops and delivers reliable enterprise-class real-time communications.

#### Key Features and Benefits

- Works with VoIP, traditional telephone lines, ISDN BRI, E1/T1/PRI, and GSM/CDMA/3G
- Built-in call recording capability
- Powerful Apps (add-ons) include Auto Provision, LDAP, and more coming soon
- Free lifetime upgrade and above all, its' super easy
- Connect multiple sites and remote users instantly
- No hidden charges and extra licensing fees
- Low power consumption (1.8-59.1 watt)

**Netregy Systems Sdn Bhd** (527446-K)

No. 26 Pusat Perdagangan One Puchong | Jalan OP 1/3 | Off Jalan Puchong | 46170 Selangor | Malaysia

Tel: +603-8070 7770 | Fax: +603-8070 7700 | enquiry@netregy.com | www.netregy.com | fb.com/netregy



## FEATURES

- Automated Attendant (IVR)
- Attended Transfer
- Blind Transfer
- Blacklist/Whitelist
- Call Back
- Call Detail Records (CDR)
- Call Forward
- Call Monitor
- Call Parking
- Call Pickup
- Call Recording
- Call Routing
- Call Waiting
- Caller ID
- Conference
- Dial by Name
- DISA
- Distinctive Ringtone
- DNIS
- Do Not Disturb (DND)
- Event Center
- Email to SMS/SMS to Email
- Fax to Email
- Follow me
- Intercom/Zone Intercom
- LDAP
- Mobility Extension
- Multi-language System Prompt
- Multi-language Web GUI
- Music on Hold
- Music on Transfer
- One Touch Recording
- Queue
- PIN List
- Phone Provisioning
- Real-time Status Monitor
- Ring Group
- Skype Integration
- Speed Dial
- User Portal
- User Privileges
- Video Calls
- Voicemail
- Voicemail to email
- Voicemail Forwarding

## SPECIFICATIONS

|                       | S20  | S50                             | S100                         | S300                        |
|-----------------------|--|---------------------------------|------------------------------|-----------------------------|
| Users                 | 20   | 50                              | 100 (up to 200)              | 300 (up to 500)             |
| Max Concurrent Calls  | 10   | 25                              | 30 (up to 60)                | 60 (up to 120)              |
| Max Analog Ports      | 4  | 8                               | 16                           | 24                          |
| Max BRI Ports         | 4  | 8                               | 16                           | 24                          |
| Max Cellular Ports    | 1  | 4                               | 6                            | 6                           |
| Max E1/T1/J1 Ports    | x  | x                               | 2                            | 3                           |
| VoIP Trunks           | 20   | 50                              | 100                          | 100                         |
| Protocol              | SIP (RFC3261), IAX2  |                                 |                              |                             |
| Transport Protocol    | UDP, TCP, TLS, SRTP  |                                 |                              |                             |
| Audio Codec           | G711 (alaw/ulaw), G722, G726, G729A, GSM, Speex, ADPCM, iLBC   |                                 |                              |                             |
| Video Codec           | H263, H263P, H264, MPEG4   |                                 |                              |                             |
| DTMF                  | In-band, RFC4733, RFC2833, SIP INFO  |                                 |                              |                             |
| LAN                   | 1 x 10/100 Mbps  | 1 x 10/100/1000 Mbps            |                              |                             |
| WAN                   | 1 x 10/100 Mbps  | 1 x 10/100/1000 Mbps            |                              |                             |
| IP Services           | Static IP, DHCP, VPN, Firewall, VLAN, DDNS, PPPoE, QoS, Static NAT, STUN   |                                 |                              |                             |
| Voicemail             | 5000 min (expandable)  |                                 | 10000 min (expandable)       |                             |
| Firewall              | Yes  | Yes                             | Yes                          | Yes                         |
| T.38 Fax              | Yes  | Yes                             | Yes                          | Yes                         |
| App Center            | Yes  | Yes                             | Yes                          | Yes                         |
| External Storage      | TF Card  | SD Card                         |                              | SD Card & 2.5 inch SATA HDD |
| USB                   | x  | x                               | 1                            | 1                           |
| Power                 | DC 12V 1A  | AC 100-240V 50/60HZ<br>0.6A max | AC 100-240V 50/60HZ 1.8A max |                             |
| Size (L x W x H) (cm) | 16 x 16 x 3  | 34 x 21 x 4.4                   | 44 x 25.2 x 4.4              | 44 x 25.2 x 4.4             |
| Weight                | 0.3 kg   | 1.48 kg                         | 2.5 kg                       | 2.6 kg                      |
| Power Consumption     | 1.8-10.6 W   | 2.1-18.5 W                      | 5.5-41.2 W                   | 6.2-59.1 W                  |
| Environment           | Operation Range: 0°C to 40°C, 32°F to 104°F; Storage Range: -20°C to 65°C, -4°F to 149°F;<br>Humidity: 10-90% non-condensing |                                 |                              |                             |
| Mounting              | Desktop  | 1U Rack-mount                   |                              |                             |